

SPECIFICATION SOLUTIONS

DURATEC[®]

POWDERCOAT RANGE



SUPER DURABLE
POLYESTER



SOLID COLOUR
LOOK



PEARLESCENT
LOOK



BRIGHT
LOOK



TEXTURED
LOOK

Reaction to fire test results

Dulux[®]

**POWDER
COATINGS**

Worth doing, worth Dulux.[®]

Worth doing, Worth Dulux.®

DURATEC®

POWDERCOAT RANGE

Two industry standard 'reaction-to-fire' tests have been carried out for the Dulux Duratec Premium Powder coat range in accordance with the Australian and New Zealand building codes to determine the Group Number Classification and Ignitability, Spread of Flame, Heat Evolved and Smoke Developed Indices.

The project: TLC Aged Care
Location: Clifton Hill, Victoria, Australia
Photo credit: Kane Jarrod Photography



Test results

Industry Standard: AS/NZS1530.3					
Methods for fire tests on building materials, components and structures Part 3: Simultaneous determination of ignitability, flame propagation, heat release and smoke release					
Standard	This Standard sets out a test method for the assessment of building materials and components to measure their behaviour and contribution to the progress of fire and further spread of it. These include:		(a) their tendency to ignite; (b) their tendency to propagate flame; (c) the heat they release once ignition has occurred; and (d) their tendency to release smoke.		
Purpose	Dulux Powder Coatings has undertaken independent testing in accordance with AS/NZS 1530.3 to allow consumers and/or regulatory bodies to determine the suitability of its architectural grade coating systems for aluminium coated extrusions, sheets, claddings, fixings, components, etc with regards to the fire hazard of the coating. The test results outlined below are specific to Dulux Duratec super durable polyester architectural grade powder coat finishes.				
Regulatory Indices	Index	Ignitability Index	Spread of Flame Index	Heat Evolved Index	Smoke Developed Index
	Range	(0-20)	(0-10)	(0-10)	(0-10)
	Score	0	0	0	3
Results Analysis	According to NCC (National Construction Code) volume one specification C1.9 e (v) of the Building Code of Australia (BCA) 2019, Duratec may be used wherever a non-combustible material is required on pre-finished or powder coated metal sheeting having a combustible surface finish not exceeding 1mm thickness and where the Spread-of-Flame Index of the product is not greater than 0. The specimen was tested on a Group 4 (least reactive) substrate as specified by Clause 4.4.3 of AS1530.3. These results only apply to any substrate in the same group or a less reactive material. The results of this fire test may be used to directly assess fire hazard, but it should be recognized that a single test method will not provide a full assessment of fire hazard under all fire conditions.				

Industry Standard: AS 5637.1		
Determination of Fire Hazard Properties – Wall & Ceiling linings		
Standard	The standard sets out procedures for the assessment of wall & ceiling linings to provide means for the determination of a Group Number Classification according to:	(a) their tendency to ignite; (b) their tendency to release heat once ignition has occurred; (c) their tendency to cause flashover; (d) their tendency to release smoke; and (e) their contribution to fire growth.
Purpose	Dulux Powder Coatings has undertaken independent testing to determine the Group Number Classification Group Number Classification in accordance with the New Zealand Building Code Calculations were carried out according to NZBC Verification Method C/VM2 Appendix A. The classification for the sample is given in the table below. Group Number Classification in accordance with NCC Australia Calculations were carried out according to AS5637.1. The Group Number Classification and Average Smoke Extinction Area for the sample is given in the table below. Determination of Fire Hazard Properties The specimen was deemed suitable for testing in accordance with AS 5637.1 and testing was performed in accordance with ISO 5660 for the purposes of Group Number Classification as specified in the NCC volume one specification C1.10 of the Building Code of Australia (BCA) 2019 for the classification of wall and ceiling linings.	
Results Analysis	Building Code Document	Group Number Classification
	NZBC Verification Method C/VM2 Appendix A: Establishing Group Numbers for lining materials	1-S
	NCC Volume One Specification C1.10 determined in accordance with AS 5637.1	1 The average specific extinction area was less than the 250 m ² /kg limit
Group 1 is the highest (best) classification and Group 4 is the poorest performing classification. The tests conducted according to the BCA assess the contribution that surface finishes make to the spread of fire and smoke to ensure that the building is protected from the spread of fire and smoke to allow sufficient time for the orderly evacuation of the building in an emergency.		

Further information

Detailed reports

For a copy of the detailed independent test results for Dulux Duratec Architectural Powder Coat range referring to in this document please contact your Dulux representative or call our Advice Line referring to the reports below.

	AS/NZS1530.3	AS 5637.1
Report Reference	CSIRO Product testing – Report No. FNE 11834 (November 2016)	BRANZ – Report No. FH 5532-001 ISSUE 3 (2020)

Standards

For copies of the standards referenced in this document please refer to:.

	AS/NZS1530.3	AS 5637.1
Standards Reference	To access AS/NZS1530.3 visit Australian or New Zealand Standards websites	To access AS 5637.1 visit Australian or New Zealand Standards websites

Other Dulux reaction to fire test results

For other Dulux Architectural Powder coat range test reports for reaction to fire visit:

Australia: duluxpowders.com.au/specifications or call 13 24 99

New Zealand: duluxpowders.co.nz/specifications or call 0800 800 975

Advice line

Our dedicated consultants can help simplify the specification process, saving you time and money by providing the right coating advice for your project. They can provide:

- Documented project specific specifications
- Written confirmation of your project's eligibility for an Alumi Shield™ or Steel Shield™ warranty
- Design, coating system and colour advice

For Australia call 13 24 99 or visit duluxpowders.com.au

For New Zealand call 0800 800 975 or visit duluxpowders.co.nz

Offices

Australia

Dulux Powder Coatings
1-15 Pound Road West
Dandenong South VIC 3175
T (61) 3 8787 4500

New Zealand

Dulux Powder Coatings
31B Hillside Road
Glenfield, Auckland 0627
T (64) 4 896 0911

Singapore

DGL International Powder Coatings
100 Pasir Panjang Road
#02-10, Singapore 118518
T (65) 6 8381 010

China

DGL International Powder Coatings
Room 406, No.8, Lane 1977, JinShaJiang Road Shanghai,
China, PC 200333
T (86) 21 6173 8800

